

SEQUENCE FOR **PUTTING ON (DONNING)** PERSONAL PROTECTIVE EQUIPMENT (PPE)

1. Gather & visually inspect PPE:

1 Isolation gown CAPR helmet CAPR comfort strips
1 Pair gloves CAPR disposable lens cuff (DLC) CAPR belt & battery

2. Secure belt and battery:

> Buckle in front – side clip facing upwards.

3. Check CAPR air flow:

- > Plug helmet into battery pack.
- > Verify at least 2 green lights remain lit.

4. Prepare and adjust helmet:

- > Attach comfort strips to Velcro located on the inside front and rear headbands.
- > Use knob in back of helmet to tighten. Ensure:
 - CAPR helmet front head band rests ½ inch above eyebrows & rear headband is below occipital bone.
 - Helmet is comfortably snug but not too tight.
 - Once properly fitted, loosen the helmet & remove.

5. Attach lens – with the DLC Cuff <u>facing the</u> inside of the helmet:

- > Peel off and discard the DLC protective film.
- > Attach center of DLC to center helmet post.
- > Align and snap DLC side holes to side posts.

6. Don Helmet:

- > Hold CAPR helmet by rear headband while pulling the front top edge of the DLC cuff under chin.
- > Place helmet on head; tighten with knob at rear.
- > Plug the helmet into the battery to initiate air-flow.

7. Adjust lens and cuff:

Position DLC sides perpendicular to temples and within ¼ inch of temples on each side of the head. Ensure slight tension on cuff is felt continuously while performing check.

8. Don isolation gown:

- > Put on isolation gown over uniform.
- > Fasten gown in back at neck and waist.

9. Disinfect hands

10. Don gloves:

> Don gloves and extend cuff of the gloves to cover the wrist on the isolation gown.

11. Verify PPE:

> Visually inspect PPE to ensure all items are intact.





































USE SAFE WORK PRACTICES TO PROTECT YOURSELF AND LIMIT THE SPREAD OF CONTAMINATION:

✓ Perform hand hygiene frequently

✓ KEEP HANDS AWAY FROM FACE AT ALL TIMES

✓ Limit surfaces touched

✓ Change gloves when torn or contaminated



SEQUENCE FOR REMOVING (DOFFING) PERSONAL PROTECTIVE EQUIPMENT (PPE)

If hands become visibly contaminated during PPE removal clean hands before continuing to remove PPE

Inside patient room

1. Ensure doffing location at least 3 feet from patient

2. Disinfect gloved hands

3. Discard gloves:

> Remove gloves only touching the outside of the first glove and the inside of the second. Discard in waste bin.







4. Disinfect hands

5. Remove gown - avoid touching front/outer surface:

- > Unfasten gown ties.
- > Grab gown at shoulder and pull forward away from neck.
- > Touching only the inside, turn gown inside out & roll it up.
- > Discard gown in waste bin.










6. Disinfect hands

In the ante room or immediately outside of the patient's room if no ante room present

7. Don gloves

8. Set up CAPR disinfection area:

Place several Sani wipes on a flat surface where you can rest your CAPR without contaminating the area.



9. Remove CAPR:

- Unplug battery.
- > Loosen the adjustment knob at the back of the helmet.
- > Tilt forward, then lift helmet off head with a forward motion.
- > Place CAPR on top of the Sani wipes.



10. Remove DLC while the helmet rests on the Sani wipes

- > Free the DLC from the posts of the helmet one at a time.
- > Discard DLC in waste bin.





11. Disinfect gloved hands

12. Doff battery/belt & disinfect CAPR assembly:

- Remove belt and battery.
- Discard comfort strips.
- > Use EPA approved disinfectant wipes to disinfect helmet, cord, battery, and belt.





13. Doff gloves

14. Perform hand hygiene

15. Return the CAPR helmet, battery, and belt to the designated area

